



Sun Shade Elite 95% & 90%

by PROVEEDORA DE LONAS Y SERVICIOS SA DE CV



Technical data Sun Shade Elite 95%

- 100% High Density Polyethylene (HDPE)
- U.V. Stabilized
- Heat-setted
- Roll Size: 9ft. 10 in. (3m) x 131ft. 2.8 in. (40m)
- 10 oz/sq yd (325 gsm) (+/-5%)
- Packing: Center-folded roll packing
- 10 years U.V. Warranty
- FR Treatment: Available depending on request
- Fabric Yarn: mono filament and Tape Yarn with U.V. Treatment
- Tensile strength (ASTM D 5034:2001 C.R.E. Grab Method) length: 1032, width: 1756
- Elongation (ASTM D 5034:2001 C.R.E. Grab Method) length: 93.7, width: 56.1

Technical Data Sun Shade Elite 90%

- 100 % High Density Polyethylene HDPE
- U.V. Stabilized
- Heat-setted
- Lock Stitch knitted tape+ monofilament yarn
- Wide: 9ft. 10 in. (3m)
- Length: 131Ft 2.8 in (40 mts.)
- 9.6 oz/sq yd (200 gsm) (+/-5%)
- Packing: Center-folded roll packing
- 10 years U.V. Warranty
- FR Treatment: Available depending on request
- Fabric Yarn: mono filament and Tape Yarn with U.V. Treatment
- Tensile strength (ASTM D 5034:2001 C.R.E. Grab Method) length: 565, width: 849
- Elongation: (ASTM D 5034:2001 C.R.E. Grab Method) length: 50.9, width: 53.2
- Bursting Strength (ASTM D 3787:2001, Ball Bursting Method) 1166

APPLICATIONS: COMMERCIAL SHADE SAIL, CANOPIES, SHADE CLOTH, PULL COVER, PRIVACY SCREEN

